



## SCMI 00ASL PRO : 3 - way active

- Features
- 25mm soft dome tweeter.
  - Full "SL" spec 12"/314mm bass driver.
  - ATC 75mm "Super Dome" mid driver.
  - On board ATC grounded plane 350W Tri-amplifier.
  - LF contour control.
  - Clip indication.
  - 6 year warranty.

## Specifications

**Drivers :** HF 25mm, Mid 75mm, LF 314mm    **Amplitude Linearity ( $\pm 2\text{dB}$ ) :** 65Hz-17kHz    **Cut-off Frequencies ( $-6\text{dB}$ , free-standing) :** 32Hz, 22kHz  
**Horizontal Dispersion :**  $\pm 80^\circ$ , Coherent    **Vertical Dispersion :**  $\pm 10^\circ$ , Coherent    **Max. Continuous SPL (1 metre) :** 115dB    **Crossover Frequencies :** 380Hz, 3.5kHz  
**Input Connectors :** Male XLR    **Input Sensitivity :** 1V    **Input Sensitivity Trim :**  $\pm 6\text{dB}$     **Input Impedance :** Balanced  $> 10\text{k}\Omega$   
**Amplifier Output :** Bass 200W, Mid 100W, High 50W    **Filters :** Even Order Critically Damped  
**Overload Protection :** Active FET momentary gain reduction plus thermal tweeter protection    **Front Panel Indicators :** Power On indicator, Gain Reduction warning  
**LF EQ :** +6dB @ 40Hz    **Dimensions (HxWxD) :** 832 x 398 x 581mm (32.8" x 15.7" x 22.9") Depth with amplifier at rear adds 3"    **Weight :** 65kg / 143lbs

Passive versions available. ATC reserves the right to vary products and specifications without prior notice.

